

## EU Declaration of Conformity

Product: IEC Miniature Circuit Breakers

Name and address of the manufacturer: Name and address of the authorised representative:

Rockwell Automation Inc.

Rockwell Automation B.V.

Rivium Promenade 160

Milwaukee, WI 53204

Rockwell Automation B.V.

Rivium Promenade 160

2909 LM Capelle aan den Ijssel

U.S.A. The Netherlands

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration: Allen-Bradley 188-J Series

(reference the attached list of catalogue numbers)

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

2014/35/EU Low Voltage Directive (LVD) 2011/65/EU RoHS Directive (RoHS)

References to the relevant harmonised standards used or references to the other technical specifications in relation to

which conformity is declared:

A11:2005 + A13:2012

EN 60898-1:2003 + A1:2004 + Electrical accessories – Circuit breakers for overcurrent protection for

household and similar installations – Part 1: Circuit breakers for a.c.

operation

EN 50581:2012 Technical documentation for the assessment of electrical and electronic

products with respect to the restriction of hazardous substances

Signed for and on behalf of the above named manufacturer:

Place and date of issue: Milwaukee, WI USA 27-June-2017

Name, function: Daniel L. Nachtigall, Technical Leader – Product Certification Engineering

Daniel L. Nachtigall

Signature:

Document Control Number: LCC-0200-C-EN



Catalogue number	Series 1	Description			
188-Jxxxx-x		IEC miniature circuit breakers per Nomenclature			

<sup>1)</sup> If no series number is given, then all series are covered

## NOMENCLATURE

	188	-	J	1	В	080	ı	N
Ī	1		2	3	4	5		6

1	Product Line						
1	188 – Miniature circuit breakers						
2	Designates Interrupting Rating						
	J-10  kA						
3	Designates Number of Poles						
	1 – 1 pole						
	2-2 pole						
	3-3 pole						
4	Designates Trip Code						
	B – Trip Curve B						
	C – Trip Curve C						
	D – Trip Curve D						
5	Designates Current Ra	ting (*C and D trip curves	s only)				
	005 – 0.5 A*	040 - 4 A*	130 – 13 A	320 - 32  A			
	010 – 1 A*	060 - 6  A	160 – 16 A	400 - 40  A			
	020 – 2 A*	080 - 8 A	200 - 20  A	500 - 50  A			
	030 – 3 A*	100 - 10  A	250 - 25  A	630 – 63 A			
6	Designates Neutral Pol	le					
	Blank – No neutral pole						
	N – Neutral pole provided						